

# pco.panda 26 DS

the new dimension in sCMOS double imaging

**double shutter**  
interframing time 1  $\mu$ s

**dust-protected**  
housing

**high resolution**  
5120 x 5120 pixels

**ultra compact**  
design

**true charge domain**  
global shutter



**DS** double shutter  
**sCMOS**

**pco.**

An Excelitas Technologies Brand

# pco.panda 26 DS

DS double shutter  
sCMOS

## Two distinct 26 MPixel images with an interframing gap as low as 1 $\mu$ s?

The outstanding global shutter capabilities of the **pco.panda 26 sCMOS** sensor make it a perfect candidate for effective **double imaging** – a prerequisite to perform all types of **Particle Image Velocimetry** measurements in flow analysis. In **PIV**, light scattering particles are added to the flow under test. A laser beam is formed into a light sheet, illuminating the scattering particles twice with a short pulse at a time interval  $\Delta t$ . The lower limit for this time interval is defined by the **double shutter interframing time** of the camera. The scattered light is recorded onto two consecutive frames of a high resolution digital camera. The shorter the **double shutter interframing time**, the higher the flow speeds which can be analyzed.

technical table	resolution	pixel size	exposure time	double shutter interframing time	frame rate	dynamic range	parasitic light sensitivity	quantum efficiency	data interface
pco.panda 26 DS	5120 x 5120	2.5 x 2.5 $\mu$ m	6 $\mu$ s to 350 ms	1 $\mu$ s **	6 fps *	66 dB	1 : 10,000	up to 65 %	USB 3.1 Gen 1
	1 fps **								
	12 fps *								
	6 fps **								

\* single shutter mode

\*\* double shutter mode

Principled timing scheme for a pco.panda 26 DS in double shutter mode used for PIV measurements





Image material with courtesy of ILA 5150



The duration of the first exposure time can be configured. The duration of the second exposure time is fixed and pre-defined by the readout time of the first image. Therefore, it is usually necessary to prevent the sensor from ambient light during the prolonged second exposure time.

sCMOS cameras

pco europe  
+49 9441 2005 50 | info@pco.de | pco.de

pco america  
+1 866 678 4566 | info@pco-tech.com | pco-tech.com

pco asia  
+65 6549 7054 | info@pco-imaging.com | pco-imaging.com

pco china  
+86 512 67634643 | info@pco.cn | pco.cn

subject to changes without prior notice © Excellitas PCO GmbH, Kelheim | pco.panda 26 DS product flyer | v1.02