

# FS5

Spectrofluorometer



The FS5 v2 is a high-performance, fully integrated spectrofluorometer designed for demanding research and analytical applications.

This compact benchtop system offers flexible source and detector configurations, adapting seamlessly to your needs.

Standard features include a photon-counting PMT detector for visible fluorescence and an absorption detector. Easily upgradeable, it supports NIR measurements up to 2050 nm, time-resolved fluorescence, phosphorescence, quantum yields, and anisotropy.

## Key Features



**12,000:1**

Water Raman SNR, high sensitivity allows for detection of very weak fluorescence signals



**Multiple detector ports**

Two emission ports and NIR upgradeability makes the FS5 unique in its class



**Rapid data acquisition**

For steady state & lifetime



**Plug & Play**

Sample modules for easy setup and flexibility



**Two in One**

Fluorescence and absorption measurements as standard



# SPECIFICATIONS

<b>STANDARD CONFIGURATION</b>	Optics	All-reflective
	Detection Technique	Single Photon Counting
	Light Source	150 W Xenon arc lamp
	Monochromators	Czerny-Turner design with dual grating turret
	Spectral Coverage - Excitation	<230 nm - 1000 nm
	Spectral Coverage - Emission	200 nm - >870 nm
	Filter wheels	Fully automated and included as standard
	Bandpass - Excitation/Emission	0 - 30 nm, continuously adjustable
	Wavelength Accuracy	± 0.5 nm
	Scan Speed - Excitation/Emission	100 nm/s
Integration Time	from 1 ms	
<b>DETECTORS</b>	Emission Detector	Cooled Single Photon Counting, PMT-900, 200 nm - 870 nm
	Reference Detector	UV enhanced silicon photodiode, 200 nm - 1000 nm
	Absorbance Detector	UV enhanced silicon photodiode, 200 nm - 1000 nm
<b>SENSITIVITY</b>	Signal-to-Noise Ratio	>12000:1 *
	Water Raman measurement (SQRT method). $\lambda_{ex}$ = 350 nm, bandpass = 5 nm, step size = 1 nm, integration time = 1 s, $\lambda_{peak}$ = 397 nm, noise measured at 450 nm	
<b>DIMENSIONS</b>	W x D x H	104 cm x 59 cm x 32 cm
	Weight	65 kg

## Upgrade Specifications

<b>EXCITATION WAVELENGTH EXTENSION</b>	Model	<b>UV+</b>			
	Excitation Coverage	<200 nm – 1000 nm			
<b>EMISSION WAVELENGTH EXTENSION</b>	Upgrade	<b>PMT-EXT</b>	<b>PMT-UC</b>	<b>NIRA1650</b>	<b>NIRA2050</b>
	Type	PMT Replacement	Additional Detector	Additional Detector	Additional Detector
	Emission Coverage	200 nm ->980 nm	200 nm - 1010 nm	870 nm ->1650 nm	870 nm ->2050 nm
	Lifetime possible	From ~90 ps	From ~120 ps	Spectral only	Spectral only
	Upgrade	<b>NIRT1400-TE</b>	<b>NIRT1700-TE</b>	<b>NIRL1400-LN</b>	<b>NIRL1650-LN</b>
	Type	Additional detector	Additional detector	Additional detector	Additional detector
	Emission Coverage	950 nm - 1400 nm	950 nm - 1650 nm	500 nm - 1400 nm	500 nm - 1650 nm
	Lifetime possible	From ~70 ps	From ~70 ps	From ~120 ps	From ~120 ps
<b>POLARISATION / ANISOTROPY</b>	Upgrade	<b>POL</b>			
	Spectral Coverage	220 nm - 900 nm excitation 240 nm - >2000 nm emission			
<b>PHOSPHORESCENCE LIFETIME</b>	Upgrade	<b>MCS</b>		<b>MCSL</b>	
	Lifetime Range (Source dependent)	<5 $\mu$ s - >10 s		50 ns - >10 s	
<b>FLUORESCENCE LIFETIME</b>	Upgrade	<b>TCSPC</b>		<b>TCSPC++</b>	
	Lifetime Range (Source dependent)	90 ps - >10 $\mu$ s		<25 ps - 10 $\mu$ s	



超高真空・極低温走査型プローブ顕微鏡  
高速分光測定装置、クライオスタット



Nd:YAGレーザー、Ti:Sレーザー  
OPOLレーザー

- 本カタログに記載されている内容は、改良のため予告無く変更する場合があります。（製品の仕様、性能、価格などはカタログ発行当時のものです）
- 本カタログに記載されている内容の一部または全部を無断で転載することは禁止されております。
- 本カタログに記載されているメーカー名、製品名などは各社の商標または登録商標です。