

5795 DE GASPE AVENUE, #222 MONTREAL, QUEBEC, H2S 2X3 CANADA

# GRAND-EOS<sup>™</sup> HYPERSPECTRAL CAMERA



Macro-imaging modality



Micro-imaging modality

TECHNICAL SPECIFICATIONS		
	GRAND-EOS	
Spectral Range	400 - 1700 nm	
	VNIR	SWIR
Spectral Resolution	< 2.5 nm (400-1000 nm)	< 4 nm (900-1700 nm)
Spatial Resolution	< 7.5 µm	< 12 µm
(with 10 X microscope objective)		
Camera	Front-illuminated interline CCD camera	
Sample Holder	XY Manual translation stage (50 mm travel)	
Wavelength tuning speed	60 ms stabilization time for 2 nm step	
Wavelength Absolute Accuracy	< 0.3 nm	
Visualisation Camera	Monochrome or Color XMP camera	
	2/3" 5.1M Progressive Color CMOS / 2448 x 2048 pixels	
Preprocessing	Spatial filtering, statistical tools, spectrum extraction, data	
	normalization, spectral calibration	
Hyperspectral Data Format	FITS, HDF5,	
Single Image Data Format	JPG, PNG, TIFF, CSV, PDF, SGV	
Software	PHySpec control and analysis software included	
Macro-imaging modality		
Field of view	Optimized from 20 x 20 mm to 160 x 160 mm	
Micro-imaging modality		
Microscope	Upright or Inverted	
Objectives	5x, 10x (other magnifications available upon request)	
Illumination	Broadband and monochromatic illumination available via	
	light guide	
Excitation	532 nm, 660 nm, 785 nm, or 808 nm lasers.	
	Other wavelengths avaiblable upon request	

GRAND-EOS combines a hyperspectral microscopy system with a hyperspectral wide-field imaging platform, giving access to micro and macro modalities with both VNIR (400-100 nm) and SWIR (900-1700 nm) spectral ranges. This imaging platform takes advantage Photon etc's patented filtering technology based on volume Bragg grating providing a non-polarized wavelength selection with high throughput and efficiency. This filtering method allows imaging of large field-of-view, scanning through a user defined wavelength range. Using a megapixel sensor, the acquisition of filtered images provides spectral information from million of points at the surface of the sample. The versatility of GRAND-EOS as well as its high spatial and spectral resolution makes it an ideal tool for both fundamental research or industrial applications.

### **APPLICATION EXAMPLES:**

- >> Photovoltaic characterization
- » Mineral analysis

- » Forensic
- > Food and plants sorting



5795 DE GASPE AVENUE, #222 MONTREAL, QUEBEC, H2S 2X3 CANADA

# HYPERSPECTRAL IMAG NG & SPECTROSCOPIC NSTRUMENTS

Photon etc. offers state-of-the-art optical analysis solutions. Its filtering patented technology based on Bragg gratings is dominantly used in its hyperspectral imaging platforms and to create widely tunable filter covering both the visible and near-infrared spectral range. From solar cells to live cells, its fast hyperspectral imaging systems provide solutions to the most challenging industrials problems, and give researchers access to the latest innovations in optical and photonic instrumentation. In addition to its recognized hyperspectral microscopy and wide-field systems, Photon etc. has developed unique near infrared cameras specifically adapted to industrial applications. As pioneers in hyperspectral imaging and filtering, Photon etc. is driven by its clients' desires to surpass limitations in measurement and analysis.

## DISTRIBUTORS

#### FRANCE

OPTON LASER INTERNATIONAL +33 (0)1 69 41 04 05 ventes@optonlaser.com

#### SPAIN

IZASA SCIENTIFIC S.L.U. +902 20 30 80 jrecasens@izasascientific.com

#### PORTUGAL

IZASA SCIENTIFIC LDA +351 21 424 73 00 info-pt@izasascientific.com

UNITED KINGDOM & IRELAND PRO-LITE TECHNOLOGY LTD

+44 (0) 12344 36110 nick.barnett@pro-lite.co.uk

GERMANY, SWITZERLAND, AUSTRIA MD INNOVATION TECH GMBH info@md-innovationtech.com

**GERMANY, SWITZERLAND, AUSTRIA & EASTERN EUROPE** SPHEREOPTICS info@sphereoptics.de +49 (0)8152 983 78-90

#### POLAND

LABNATEK +22 119 47 17 info@labnatek.pl

#### JAPAN

TOKYO INSTRUMENT +81 3 3686 4711 sales@tokyoinst.co.jp

#### INDIA

INKARP INSTRUMENTS PVT. LTD +914027172293 harishk@inkarp.co.in

# CHINA

AUNION TECH +86 21 51083793 info@auniontech.com

WWW.PHOTONETC.COM