
**Compact Laser Module Without Compromises**

**KEY FEATURES:**

- \* Output powers up to 1W
- \* High beam quality and stability
- \* Broad selection of wavelengths and fine-tuneable
- \* Modulation up to 1.5 MHz
- \* Temperature-stabilized
- \* Wavelength-stabilized systems available
- \* Control Software Ltunes included
- \* Two different controller versions
- \* Fiber coupler & fibers available

**PowerBox laser controller**

**KEY FEATURES:**

The PowerBox is a miniaturized laser controller for the Lambda Beam series of Laser modules, providing power to the laser and controlling the emission and temperature. It is designed for industrial integration where small sizes and weights are important.

- \* Attaches directly to the laser head
- \* Highly compact design
- \* Straightforward connection via screw-type terminal block
- \* Digital control via USB (RS-232 on request)
- \* Powered by 12 - 36 V DC
- \* Modulation input analog or digital 0 - 5 V DC
- \* Interlock on/off input

Alternatively, the **PowerController<sup>RS</sup>** can be used, featuring larger connectors and a keyswitch.


**PowerController**
**Accessories e.g.**

**Fiber Coupler**


**Optical fiber cable**

**Shutter**

Type	Wavelength	Maximum output power mW
Diode	375 nm	20, 70, 200* <sup>1</sup>
Diode	395 nm	50, 120
Diode	405 nm	40, 75, 125, 175, 200, 300* <sup>2</sup> , 500* <sup>1*2</sup> , 1000* <sup>1*2</sup>
Diode	415 nm	50, 120
Diode	420 nm	50
Diode	422 nm	120
Diode	425 nm	50
Diode	430 nm	50
Diode	435 nm	50
Diode	440 nm	50
Diode	445 nm	50, 100, 500* <sup>1*2</sup> , 1000* <sup>1*2</sup>
Diode	450 nm	75, 1000* <sup>1*2</sup>
Diode	455 nm	50, 100
Diode	460 nm	50
Diode	465 nm	50
Diode	470 nm	50
Diode	473 nm	100
Diode	488 nm	50, 200
Diode	505 nm	75
Diode	510 nm	75
Diode	515 nm	25, 75
Diode	520 nm	50, 80, 120, 500* <sup>1*2</sup>
Diode	532 nm	75, 100, 125, 175, 200
DPSS	532 nm	125, 175, 200 narrow line NL
Diode	633 nm	75
Diode	635 nm	75, 125
Diode	638 nm	75, 125, 175, 250* <sup>1*2</sup> , 500* <sup>1*2</sup>
Diode	642 nm	75, 150
Diode	650 nm	150* <sup>1</sup>
Diode	660 nm	75, 120, 200
Diode	670 nm	15, 250 * <sup>1*2</sup>
Diode	675 nm	200
Diode	685 nm	40
Diode	690 nm	30
Diode	705 nm	40
Diode	730 nm	40
Diode	760 nm	10
Diode	780 nm	50
Diode	785 nm	100, 200, 300* <sup>2</sup> , 400* <sup>2</sup>
Diode	805 nm	500* <sup>1*2</sup>
Diode	808 nm	75, 150, 1000* <sup>1*2</sup>
Diode	820 nm	100
Diode	825 nm	200
Diode	830 nm	45, 75, 125, 225, 1000* <sup>1*2</sup>
Diode	840 nm	50, 175
Diode	852 nm	75, 125
Diode	880 nm	10
Diode	905 nm	10, 175
Diode	915 nm	75, 125, 175, 250* <sup>2</sup> , 1000* <sup>1*2</sup>
Diode	940 nm	75, 125, 175, 200* <sup>1</sup> , 250* <sup>2</sup>
Diode	980 nm	75, 125, 175, 250, 1000* <sup>1*2</sup>
Diode	1064 nm	125, 175, 300* <sup>2</sup> , 450* <sup>2</sup> , 1000* <sup>1*2</sup>

**Lambda Beam Wavelock™**  
**Highly stabilized compact laser system**

Wave-length	max. output power mW	Coherence length
405 nm	12, 25, 40	> 1.0 m
633 nm	40, 70	> 10.0 m
638 nm	120	> 2.0 m
640 nm	32	> 1.0 m
658 nm	35	> 1.0 m
685 nm	45	> 3.0 m
785 nm	100	> 1.5 m
785 nm	225	> 10.0 m
808 nm	120	> 2.0 m
808 nm	450* <sup>2</sup>	> 10.0 m
852 nm	550* <sup>2</sup>	> 10.0 m


**Miniaturized Laser Module**

**KEY FEATURES:**

- \* Incredibly small yet fully featured
- \* Output powers up to 75 mW
- \* Powered via USB: no extra power adapter required
- \* Control Software Ltunes included
- \* Excellent value for money

**Lambda Mini EVO**

Wavelength	Maximum output power mW
405 nm	15, 50
450 nm	75
488 nm	50
515 nm	25
520 nm	50
640 nm	75
660 nm	75
685 nm	40
785 nm	75
830 nm	50

**Lambda Mini FIBER**

Wavelength	Maximum output power mW
400 nm	30
405 nm	15, 50
445 nm	30, 50
460 nm	50
488 nm	30
520 nm	30, 50
635 nm	30, 50
660 nm	50
670 nm	50
705 nm	15
730 nm	15
785 nm	50
820 nm	50
830 nm	50
905 nm	50
940 nm	50
1064 nm	15
1310 nm	10
1550 nm	10



- \*<sup>1</sup> Multi-mode
- \*<sup>2</sup> Watercooler option recommended
- \*<sup>3</sup> on request

RGB Lasersystems GmbH  
 Donaupark 13  
 93309 Kelheim  
 Germany

Phone: +49 9441 1750330  
 sales@rgb-photonics.com



東京インスツルメンツ  
TOKYO INSTRUMENTS

本社: 〒134-0088 東京都江戸川区西葛西6-18-14 T.I.ビル ☎03-3686-4711  
大阪営業所: 〒532-0003 大阪府大阪市淀川区宮原4-1-46 新大阪北ビル ☎06-6393-7411  
🌐 <https://www.tokyoinst.co.jp> ✉ [sales@tokyoinst.co.jp](mailto:sales@tokyoinst.co.jp)

**TII Group Company** – グローバルにネットワークを広げ、最先端の科学をお客様に提供 –



超高真空・極低温走査型プローブ顕微鏡  
高速分光測定装置、クライオスタット



Nd:YAGレーザー、Ti:Sレーザー  
OPOLレーザー



Enviro ESCA (準大気圧XPS)  
ARPESなど

- 本カタログに記載されている内容は、改良のため予告無く変更する場合があります。(製品の仕様、性能、価格などはカタログ発行当時のものです)
- 本カタログに記載されている内容の一部または全部を無断で転載することは禁止されております。
- 本カタログに記載されているメーカー名、製品名などは各社の商標または登録商標です。