

The NeoSpectra Puck is a plug and play, compact and portable near-infrared (NIR) spectrometer which allows researchers, application developers, and others to quickly apply NeoSpectra spectroscopy solutions to an array of target applications. It enables homogenous material identification, qualification, and quantification at the point of need.



The NeoSpectra Puck core technology is based on semiconductor Micro Electromechanical Systems (MEMS) microfabrication techniques, promising unprecedented economies of scale, robustness, and consistency between devices. With its unique features of size, cost, and scalability, it enables new usage models for different application areas.

Features

- Smallest FT-NIR spectrometer solution
- Built-in illumination for reflectance sampling
- Connection to PC for viewing and saving spectra
- Wide spectral ranges in the extended NIR (λ : 1,350 – 2,550 nm) enables wider range of applications
- Low power consumption (PC powered)
- Easy to use and operate
- Software for collecting & viewing spectra

Sample Applications

The NeoSpectra Puck enables the creation of instant, accurate and cost-effective material analysis solutions for a variety of homogeneous solid or liquid samples in different application areas including:

- Food analysis: Milk composition and adulteration, flour analysis
- Agriculture: Processed feed analysis
- Pharmaceutical: Classification and quantification of raw ingredients
- Polymers: Plastic sorting, thin film analysis
- Fabrics: Classification of textiles, fabric treatment
- Other R&D applications

Specifications

Parameter	Conditions	Value
Wavelength Range	PSD > max PSD/10	1,350 – 2,550 nm
Resolution	At $\lambda = 1,550$ nm, FWHM criterion	16 nm
		66.6 cm^{-1}
Typical SNR (rms)	2 s Scan time, @ $\lambda = 2,350$ nm,	2,000:1
Temperature	Operation	23 : 104 °F (–5 : 40 °C)
Wavelength Accuracy	@ $\lambda = 1,400$ nm; temperature < 40°C	± 1.5 nm
Wavelength Repeatability	@ $\lambda = 1,400$ nm; absorbance level = 0.5 A.U., Resolution: 16 nm	± 0.15 nm
Dimensions		4 x 3.2 x 1.8 inch (10 x 8 x 4.5 cm)
Weight		1.2 lbs (550 g)
Power	3A (USB-C to A) included	USB-C connector
Connectivity	USB-C to A included	USB-C connector
Bulb lifetime	(Continuous operation)	> 10,000 hrs
Diameter of collected light beam		0.1 inch (2.5–3 mm)
PSD: Power Spectral Density – Single beam spectrum SNR is calculated from the root mean square noise (Nrms), which is the standard deviation of 100 consecutive 100% lines at each wavelength. SNR=1Nrms		

Software Specifications

USB to Windows PC & SpectroMOST® software. Cloud connectivity with NeoSpectra Data Portal.

Connectivity

Bluetooth, WiFi, USB C

Disclaimer

Information in this document is provided in connection with Si-Ware Systems products. These materials are provided by Si-Ware Systems as a service to its customers and may be used for informational purposes only. Si-Ware Systems assumes no responsibility for errors or omissions in these materials. Si-Ware Systems may make changes to its products, specifications, and product descriptions at any time, without notice. Si-Ware Systems makes no commitment to update the information and shall have no responsibility whatsoever for conflicts, incompatibilities, or other difficulties arising from future changes to its products and product descriptions. No license, express or implied, by estoppels or otherwise, to any intellectual property rights is granted by this document. Except as may be provided in Si-Ware Systems' Terms and Conditions of Sale for such products, Si-Ware Systems assumes no liability whatsoever.



グローバルにネットワークを広げ、最先端の科学をお客様に提供

本 社：〒134-0088 東京都江戸川区西葛西6-18-14 T. ビル

Tel. 03-3686-4711

営業所：〒532-0003 大阪府大阪市淀川区宮原4-1-46 新大阪北ビル

Tel. 06-6393-7411

URL : <https://www.tokyoinst.co.jp> Mail : sales@tokyoinst.co.jp



超高真空・極低温走査型プローブ顕微鏡
高速分光測定装置、クライオスタット



- 本カタログに記載されている内容は、改良のため予告無く変更する場合があります。（製品の仕様、性能、価格などはカタログ発行当時のものです）
- 本カタログに記載されている内容の一部または全部を無断で転載することは禁止されております。
- 本カタログに記載されているメーカー名、製品名などは各社の商標または登録商標です。