

# Solo 689.4 QT

## Ultra-narrow Linewidth Laser



UniKLasers supplies ultra-narrow linewidth QT Series lasers to our partners in quantum sensing, quantum metrology, and other related technologies, at the specific wavelengths related to the atomic transitions they need to target. Our QT Laser Series includes the Solo 813.42 QT and Solo 780.24 QT for Rubidium, as well as the Solo 698.4 QT and Solo 689.4 QT for Strontium.

### KEY FEATURES



**Ultra-narrow Linewidth**  
 $\leq 0.3$  MHz



**High Power Stability**  
 $\leq 2.0$  % over 8 hours



**High Spectral Stability**  
 $\pm 1$  pm over 8 hours



**Excellent Beam Quality**



**Designed for Strontium Atoms**

### APPLICATIONS

Quantum Research - Strontium

### Specifications

#### Output Beam Parameters:

Output Power	10, 20, or 30 mW*
Wavelength	689.4 nm
Spectral Bandwidth	$\leq 0.3$ MHz
Spatial Mode	TEM <sub>00</sub>
Spectral Stability	$\pm 1.0$ pm (over 8 hour operation)
Coherence Length	$> 100$ m
Output Power Stability	$\leq 2.0$ % (over 8 hour operation)
Output Power Noise	$\leq 0.1$ % RMS (10 Hz – 10 MHz)
Beam Divergence	$\leq 1$ mrad, diffraction limited
Beam Diameter at Output Aperture	0.8 – 1.2 mm
Beam Pointing Stability	$\leq 5$ $\mu$ rad/°C
Polarisation Ratio	$\geq 100:1$ , vertical

#### Integration Features:

Plug-In USB Connectivity	Combined Heatsink
Versatile Control Software	Remote Diagnostic Support

#### Laser Head Dimensions:

L x W	207 x 80 mm
Beam Height	75 mm

#### Environmental Conditions:

Ambient Temperature Range	18 – 30 °C
Laser Head Interface Stability	$\pm 1.5$ °C
Storage	0 – 50 °C
Humidity	5 – 95 %, non-condensing


#### Optional Accessories:

Heatsink	Fan-Assisted
	Water-Cooled with Thermoelectric Chiller
External Power Control Module	0 – 100 %, continuous
Tuning Range, mode-hop free	25 – 50 GHz
Low Power Alignment Beam Mode	

\* Other output powers available on request

### Laser and Heatsink Dimensions

238 x 80 x 95 mm



### CONTACT US

- ✉ info@uniklasers.com
- ☎ +44 (0)131 333 2200
- 🌐 uniklasers.com



東京インスツルメンツ  
**TOKYO INSTRUMENTS**

<https://www.tokyoinst.co.jp/>

本社：〒134-0088 東京都江戸川区西葛西 6-18-14 T. I. ビル  
TEL : 03-3686-4711 FAX : 03-3686-0831  
大阪営業所：〒532-0003 大阪市淀川区宮原 4-1-46 新大阪北ビル  
TEL : 06-6393-7411 FAX : 06-6393-7055

DESIGNED &  
MANUFACTURED  
IN THE UK



AVOID EYE OR SKIN EXPOSURE TO  
DIRECT OR SCATTERED RADIATION  
**CLASS 4 LASER PRODUCT**  
MAX. POWER: 1000 mW  
(IEC 60825-1)