


Test Report UST® - Universal Surface Tester



Würzburg, 2012-04-17

Customer:

Samples: Paper

Report no.:

Test engineer:

Report by:

Sign

Table of contents

1. General description UST®.....	3
2. Measuring principle.....	4
2.1 Deformation measurement (UST® standard measurement).....	4
2.2 Scratch test.....	6
2.3 Abrasion.....	7
2.4 Micro friction.....	8
2.5 Roughness according to DIN EN ISO 4287.....	9
2.6 Viscoelasticity / Static measurement.....	10
2.7 Damping.....	11
2.8 Universal hardness.....	12
2.9 3D topography.....	13
3. Samples.....	14
4. Results.....	15
4.1 Standard measurement with micro friction.....	15
4.2 Scratch test with micro friction.....	17
4.3 Abrasion.....	18
4.4 Micro friction.....	20
4.5 Roughness.....	21
4.6 Viscoelasticity / Static measurement.....	22
4.7 3D standard measurement.....	23
4.8 3D Topography.....	24
5. Summary.....	25
6. Appendix.....	26
6.1 Measurement window “Standard test with micro friction”.....	26
6.2 Measurement window “Scratch test with micro friction”.....	28
6.3 Measurement window “Abrasion”.....	32
6.4 Measurement window “Micro friction”.....	34
6.5 Measurement window “Roughness”.....	36
6.6 Measurement window “Static measurement”.....	38
6.7 3D standard measurement.....	39
6.8 3D topography.....	53


1. General description UST®

With the mechanical micro structure analysis (MISTAN®) procedure it is possible to determine mechanical, topographical and functional properties continuously on various surfaces.

The Universal Surface Tester UST® continuously determines the materials behavior and the corresponding deformation.

Therefore objective information can be obtained for the following material properties:

- Elasticity and plasticity
- Roughness and topography
- Total deformation
- Micro hardness
- Viscoelastic properties
- Scratch resistance
- Abrasion
- Softness/Haptics
- Compressibility
- Micro force measurement
- Material homogeneity




Universal Surface Tester UST®

2. Measuring principle

2.1 Deformation measurement (UST® standard measurement)

The MISTAN®-procedure enables variable load range scanning. During the tactile measurement a stylus is moved linear on the material surface for three times.

The topography is recorded with a z-resolution of 60nm.



MISTAN® principle

First step (red)

Scanning along a definite path on the material's surface with a minimum load of 1 mN. As a result the vertical deflection of the stylus and therefore the surface texture is continuously determined (virgin profile).

Second step (green)

The same path is now scanned with the same stylus under a defined and constant load. A deformation of the surface occurs. This is called the total deformation V_g .

Third step (blue)


In this step the same path is scanned again with a minimum load. The elastic part of the total deformation is now recovered, it is called V_e . The permanent deformation V_p is the part that does not recover.

Fourth step

The local deformation values are calculated based on the differences between the surface and deformation profiles (step 1, step 2 and step 3) and shown in the second graph window.

The measurement can be viewed online in the upper window. After it is finished the program calculates the deformation curves and displays them in the middle window.


- | | |
|--|---|
| Orange line
Green line
Light blue line | Total deformation
Elastic deformation
Permanent deformation |
|--|---|



UST® software, 2D standard measurement

2.2 Scratch test


The scratch test module is based on the MISTAN® procedure. During the second step the load is increased stepwise to a final load. Depending on the UST® version there are start and final loads between 1 mN and 1000 mN possible. The number of load steps can be chosen from 1 to 100 steps.



As a result the total as well as the permanent and elastic deformation values are given. Additionally, a statistic for each individual load step can be listed.


UST®									
Loadstep [mN]	Permanent deformation			Elastic deformation			Total deformation		
	Number of data points	Mean µm	Stand. dev. µm	Mean µm	Stand. dev. µm	Mean µm	Stand. dev. µm	Mean µm	Stand. dev. µm
10,00	496	0,67	0,995	-0,45	0,201	0,22	0,258		
22,63	446	6,58	1,416	-0,27	0,983	6,31	1,176		
35,26	446	11,00	1,055	0,02	0,956	11,02	0,918		
47,89	446	14,91	1,579	0,11	0,462	15,02	1,911		
60,53	446	15,66	4,654	0,62	0,709	16,30	4,651		
73,16	446	21,55	1,211	0,61	0,398	22,20	1,854		
85,79	446	23,73	0,937	0,75	0,361	24,48	0,726		
98,42	446	23,73	2,106	1,21	0,809	22,80	1,751		
111,05	446	24,56	1,983	1,81	1,045	26,36	2,071		
123,68	446	23,21	5,237	3,52	1,478	26,73	4,219		
Total Statistics		25,73	3,268	2,88	1,117	26,81	2,855		
UST Scratch Test		149,95	29,14	2,984	2,12	0,937	31,26	2,263	
User: Innowep		186,94	30,90	2,972	2,25	0,930	35,37	2,999	
Date of measurement: 18/02/2006, 15:31		174,21	31,57	1,533	2,17	0,959	33,74	1,454	
Comment: Mythenex Grid M0751 tongs		189,47	31,71	3,865	3,45	1,229	35,16	3,963	
212,11	446	31,03	5,977	4,95	2,209	35,99	4,247		
224,74	446	25,49	8,127	7,23	3,608	32,72	5,641		
237,37	446	34,36	3,142	4,21	1,417	38,57	3,340		
250,00	446	26,57	7,436	7,35	2,630	35,92	5,557		
0,00	0,00	0,00	0,0000	0,00	0,0000	0,00	0,0000		
0,00	0,00	0,00	0,0000	0,00	0,0000	0,00	0,0000		
0,00	0,00	0,00	0,0000	0,00	0,0000	0,00	0,0000		
0,00	0,00	0,00	0,0000	0,00	0,0000	0,00	0,0000		
0,00	0,00	0,00	0,0000	0,00	0,0000	0,00	0,0000		
Total mean:	9953	29,42	9,901	2,45	2,621	25,87	11,220		

Formation of a scratch (loss of material)



User: Innowep
Date of measurement: 14/7/2004, 11:10
Comment: Test 1

Formation of a groove (no loss of material)




User: Innowep
Date of measurement: 24/3/2004, 10:29
Comment: Sample 4

Examples for typical damages during a scratch test

2.3 Abrasion

The abrasion module is based on the MISTAN® principle though the second step under load is repeated arbitrary times. So, besides the elastic and permanent deformations also the abrasion behavior under defined parameters can be investigated.





A change of the mistan-procedure allows a repetition of the second load step (constant load) as often as wanted. The so obtained identification of deformations and amount of abraded material yields a clearly understandable locally differentiated statement for the wear resistance. All areas of interest can be zoomed out for a deeper investigation.

Additional to the three surface and deformations profiles within the standard measurement, the UST® records the last load step of the abrasion test. The difference between the first and the last load cycle gives the local value of abrasion.

2.4 Micro friction

With the additional module "Micro friction" the analysis possibilities of the Universal Surface Tester are enhanced by the measured value of friction forces. It can be used as a standalone module or be combined with the standard measurement or scratch test. The measurement table (picture on the right) is mounted on the processing table, which is applied by the friction force. The counter-body on the sample, is detected by a highly sensitive piezo sensor, which is integrated into the measuring table. The measurement module can be used for haptical as well as microtribological investigations on flat and structured surfaces. In contrast to conventional force gauges the sensor has an extremely high frequency and stiffness and is therefore able to measure highly dynamic, without proper inertia, and with an extremely high local resolution. The module enables measurements in a large effective range with high force resolution in the sub-nm regime.

In the upper window of the micro friction software module the actual profile of the surface structure is displayed. In the lower window the friction forces during measurement are displayed. When the measurement is finished the averaged friction forces and friction coefficient μ are displayed in the statistics window.




⇨ Surface structure

⇨ locally resolved, corresponding dynamic micro force signal

2.5 Roughness according to DIN EN ISO 4287

With the roughness module the roughness of a surface is evaluated according to DIN EN ISO 4287 bestimmt. The surface is scanned with a freely definable load. Afterwards the roughness values R_a , R_q and R_z are calculated automatically. With this module the roughness values can also be evaluated from previous standard, 3D standard, 3D topography, scratch or abrasion measurements.

In the upper window the surface profile is shown, in the lower window the roughness after subtraction of a linear offset and calculation with a selectable wavelength filter is displayed graphically. The statistic analysis is displayed in the lower left part of the measurement window.




The wavelength filter is chosen automatically according to the international norm. To get additional information or to calculate the roughness of small surfaces the wavelength filter can also be chosen by hand.

Additionally to the roughness values R_a , R_q and R_z the system evaluates the effective length in mm and as percentage of the total measuring distance.

2.6 Viscoelasticity / Static measurement

For assessment of the viscoelastic material properties, a selective analysis is taken out and presented as a function of time. During the load duration, a characteristic material behavior can be observed: the material resistance under load (green line). During the relief stage a period of complete resetting of the elastically deformed part can be seen (blue line). The shape of the graph enables to understand the viscoelastic character of the material.



The graph is a function of time.
Time and force of preload, load
and relief can be set by the
user.


The differences in displacement
under preload, load and relief
are stated in the statistics box.

Based on this UST® module, many hardness and viscoelasticity measurements can be done according to international standards. Depending on the applied standard, a special tip geometry may be required.

2.7 Damping

The elastic properties of soft materials can be examined especially well with the damping module. The stylus is dropped from a defined height with a defined load onto the sample surface. The height signal is recorded during fall and bouncing.


Depending on material, stylus and load the tip will bounce off the surface for a couple of times. The result is a damped oscillation, displayed in the graph window and evaluated for damping constant and mean frequency.



In the statistics windows below the graph window the falling height of the stylus, the first four damping decrements, their mean value, the damping constant and the mean frequency of oscillation are displayed.

2.8 Universal hardness

The measurement mode “Universal hardness” enables the evaluation of hardness values according to DIN EN ISO 14577-1. It consists of two steps: A predefined load will be applied to the stylus for a given time (preload). After that the load on the stylus will be increased stepwise over a predefined period. During the whole measuring time the signal of the stylus will be recorded. Finally the universal hardness is calculated from the total deformation that has been measured.



The universal hardness is given e.g. as HU 0.050/35.0/7 (see picture above) which means

HU: universal hardness measurement

0.050: final load in N (here 50 mN)

35.0: time of load in s (here 35 s)


7: number of steps (here 7)

The unit of the universal hardness is [N/mm²].

2.9 3D topography

For the 3D topography measurement the height profile is scanned over several parallel lines. The distance in y-direction between these lines is freely adjustable. During measurement the height profile of each line is shown. Afterwards, the 3D topography is shown but can be switched to a 2D view of each line. In the lower left corner the statistics of the roughness values can be found.

In a special height cut mode it is possible to evaluate particles and porosity.



3. Samples

We received nine different paper samples which were labeled as follows:

Sample	Reel
AAA	12345-6
BBB	4567-8
CCC	9875-8
DDD	24563-2
EEE	12587-4
FFF	135748-6
GGG	136587-5
HHH	35896-7
III	1238579-4

We made five measurements on the coated side and two measurements on the uncoated side. Each area of a measurement was marked with a square, the measurement itself was done inside of it. Each square was numbered.

For these UST measurements we chose two samples, CCC and FFF, and did measurements on the coated side.

4. Results

4.1 Standard measurement with micro friction

The measurement with the module “Standard measurement with micro friction” was performed with the following parameters:

Module	Standard measurement with micro friction
Stylus	steel cone, 60°
Zero load [mN]	1
Load [mN]	50
Distance [mm]	5
Pre- and post scan [mm]	0.5
Velocity [mm/s]	0.1
Increment [μm]	1.98

Sample CCC


The measurement gave the following results, averaged over 2524 single points:

#	Deformations						Friction force	
	Permanent [μm]	σ [μm]	Elastic [μm]	σ [μm]	Total [μm]	σ [μm]	Force [mN]	σ [mN]
1	2.44	0.61	4.96	0.88	7.40	1.30	25.31	2.63
2	3.04	0.61	5.43	1.06	8.47	1.47	26.83	2.83
3	2.88	0.68	5.16	0.74	8.04	1.11	26.29	3.00
Average	2.79	0.31	5.18	0.24	7.97	0.54	26.14	0.77

Sample FFF

The measurement gave the following results, averaged over 2524 single points:

#	Deformations						Friction force	
	Permanent [µm]	σ [µm]	Elastic [µm]	σ [µm]	Total [µm]	σ [µm]	Force [mN]	σ [mN]
1	2.84	0.48	5.15	1.02	7.98	1.22	15.82	2.51
2	2.42	0.45	5.26	0.82	7.68	1.00	16.46	2.19
3	2.26	0.57	4.21	1.07	6.47	1.41	16.13	2.46
Average	2.51	0.30	4.87	0.58	7.38	0.80	16.14	0.32



Both deformations, elastic and permanent, are about 10 % higher on paper CCC. This could be due to the greater thickness of the paper. The standard deviation of paper FFF, especially of the elastic deformation, is significantly higher than of paper CCC. So, the material structure of paper FFF seems to be much more inhomogeneous.

The ratio between permanent and elastic deformation is about 1:2.

The difference in micro friction forces is much greater. The forces between paper and stylus on paper CCC are about 50 % higher than on paper FFF. So, the surface of paper CCC is more sticky, the surface of paper FFF is slicker.


4.2 Scratch test with micro friction

The measurement with the module “Scratch test with micro friction” was performed with the following parameters:

Module	Scratch test with micro friction
Stylus	Scratch diamond
Zero load [mN]	1
Start load [mN]	1
End load [mN]	10
No. of load steps	10
Distance [mm]	5
Pre- and post scan [mm]	0.5
Velocity [mm/s]	0.1
Increment [μm]	1.98

In the following table the deformations of the highest load step at 10 mN are given. At this load step the result is averaged over 228 single points:

Sample	Deformations						Friction force	
	Permanent [μm]	σ [μm]	Elastic [μm]	σ [μm]	Total [μm]	σ [μm]	Force [mN]	σ [mN]
CCC	4.76	3.88	1.10	0.79	5.86	3.38	14.07	4.46
FFF	7.78	1.90	0.61	0.38	8.38	1.83	19.87	2.36



Although the load of 10 mN is much lower than in the “Standard measurement with micro friction” (50 mN) the permanent deformation and hence the damage of the coating is much greater. The ration between elastic and permanent deformation changed from 2:1 to 1:4 on paper CCC and 1:13 on paper FFF respectively. Although the coating on paper CCC seems to be much thicker the permanent deformation is not as great as on paper FFF. So, this coating is much more scratch resistant. But the large standard deviations, especially on paper CCC, are an indication that the dynamic process of scratching is in full motion.

The micro friction forces show a different behavior than in the “Standard measurement with micro friction”. Here, the forces on paper FFF are significantly higher. But this is due to the scratch process. The stylus is sinking deep into the coating thus the contact area between sample and stylus is much bigger resulting in higher friction forces.


4.3 Abrasion

The measurement with the module “Abrasion” was performed with the following parameters:

Module	Abrasion
Stylus	Steel cone 60°
Zero load [mN]	1
Load [mN]	50
Distance [mm]	5
Pre- and post scan [mm]	0.5
Velocity [mm/s]	0.1
Increment [μm]	2.01
No. of cycles under load	10

The measurement gave the following results, averaged over 2488 single points:

Sample	Deformations							
	Permanent [μm]	σ [μm]	Elastic [μm]	σ [μm]	Total [μm]	σ [μm]	Abrasion [μm]	σ [μm]
CCC	5.56	0.72	5.00	0.50	7.85	0.82	2.71	0.32
FFF	3.70	0.83	4.24	0.71	6.16	0.98	1.78	0.40



Just like in the “Standard measurement with micro friction” the deformations of paper CCC are greater than of paper FFF. The difference between the two papers are now greater due to the 10 times repeated load step. When using a steel cone stylus, no coating material has been abraded. The abrasion value is a measure for the degree of deformation during the 10 load steps. Paper CCC has a greater abrasion which is presumably due to the higher thickness of the coating.

4.4 Micro friction

The measurement with the module “Micro friction” was performed with the following parameters:

Module	Roughness
Stylus	Papillary stylus
Load [mN]	50
Distance [mm]	5
Pre- and post scan [mm]	0.5
Velocity [mm/s]	0.1
Increment [μm]	1.98

For this measurement a special haptics stylus was used. It is made of silicon rubber and has a special groove structure which simulates the human fingertip.

The measurement gave the following results, averaged over 2524 single points:



Sample CCC

#	Friction force [mN]	σ [mN]
1	52.73	1.22
2	54.11	1.53
3	55.89	1.52
Average	54.24	1.58

Sample FFF

#	Friction force [mN]	σ [mN]
1	49.40	1.76
2	47.46	0.91
3	49.33	1.07
Average	48.73	1.10

Paper CCC has significantly higher micro friction forces.

4.5 Roughness

The measurement with the module “Roughness” was performed with the following parameters:

Module	Roughness
Stylus	Steel cone 60°
Load [mN]	1
Distance [mm]	5
Pre- and post scan [mm]	0.5
Velocity [mm/s]	0.1
Increment [μm]	1.98

A wavelength filter of 0,80 mm was used. The measurement gave the following results, averaged over 1715 single points:

Sample CCC

#	Roughness values		
	R_a [μm]	R_q [μm]	R_z [μm]
1	0.717	0.907	3.580
2	0.918	1.257	4.470
3	0.850	1.064	4.183
Average	0.828	1.076	4.078

Sample FFF

#	Roughness values		
	R_a [μm]	R_q [μm]	R_z [μm]
1	0.563	0.691	2.977
2	0.447	0.562	2.421
3	0.618	0.790	3.552
Average	0.543	0.681	2.983

Paper CCC is significantly rougher than paper FFF.

4.6 Viscoelasticity / Static measurement

The measurement with the module “Static measurement” was performed with the following parameters:

Module	Static measurement
Stylus	Aluminum ball, Ø 20 mm
Time preload [s]	300
Load preload [mN]	1
Time load [s]	3600
Load [mN]	100
Time relief [s]	1800
Load relief [mN]	1
Frequency [Hz]	100

The measurement gave the following results:

Sample	Viscoelasticity		
	Difference load [µm]	Difference relief [µm]	Ratio load / relief [%]
CCC	8.30	6.35	76.51
FFF	8.61	4.09	47.50

The creeping and recovery processes on paper FFF occur much faster and abrupt than on paper CCC. This could be due to the lower thickness of the paper and the coating. The absolute relief of paper CCC is 50 % higher than of paper FFF. This confirms the result of the “Scratch test with micro friction”. Here and there is the permanent deformation of paper CCC lower.


4.7 3D standard measurement

The measurement with the module “3D standard measurement” was performed with the following parameters:

Module	3D standard measurement
Stylus	Steel cone 60°
Zero load [mN]	1
Load [mN]	50
Distance x direction [mm]	5
Distance y direction [mm]	5
Pre- and post scan [mm]	0.5
Velocity [mm/s]	0.25
Increment x direction [μm]	2.01
Increment y direction [mm]	0.02

The measurement gave the following results, averaged over 624739 single points:

Sample	Deformations					
	Permanent [μm]	σ [μm]	Elastic [μm]	σ [μm]	Total [μm]	σ [μm]
CCC	2.10	0.51	5.10	0.76	7.20	1.08
FFF	2.40	0.57	5.51	1.17	7.91	1.46



These values not only confirm the results of the “Standard measurement with micro friction”, they should also be more accurate because of the bigger data basis.

4.8 3D Topography

These measurements were done on the same spot as one of the TRACEiT® measurements for direct comparison. On paper CCC the test was performed in square 4 and on paper FFF in square 5.

The measurement with the module “3D topography” was performed with the following parameters:

Module	3D topography
Stylus	Steel cone 60°
Load [mN]	50
Distance x direction [mm]	5
Distance y direction [mm]	5
Pre- and post scan [mm]	0.5
Velocity [mm/s]	0.25
Increment x direction [μm]	2.01
Increment y direction [mm]	0.02

From the topographies, the roughness values R_a , R_q and R_z are calculated over 251 lines:

Sample	Roughness values					
	R_a [μm]	σ [μm]	R_q [μm]	σ [μm]	R_z [μm]	σ [μm]
CCC	0.86	0.12	1.08	0.15	4.16	0.55
FFF	0.56	0.06	0.70	0.08	2.97	0.33

These values not only confirm the results of the “Roughness measurement”, they should also be more accurate because of the bigger data basis.

5. Summary

One of the advantages of the UST® is the comparative measurement. Measuring different samples, the properties, advantages and disadvantages of the material structure can be clearly determined *in situ* and with high local resolution.


Die zur Verfügung stehende Probe wurde exemplarisch mit dem UST® hinsichtlich ihrer funktionalen Systemeigenschaften untersucht. Dafür wurden insgesamt sechs Module verwendet. Alle Module konnten problemlos durchgeführt werden und zeigten keine Messfehler.

For questions concerning the results, the UST® apparatus or further investigations you can ask us at any time.


6. Appendix

6.1 Measurement window “Standard test with micro friction”

Sample CCC (example)




Sample FFF




6.2 Measurement window “Scratch test with micro friction”

Sample CCC



UST ®													
Total Statistics UST Scratch Test and Micro friction Loads/mN 1,00 2,00 3,00 4,00 5,00 6,00 7,00 8,00 9,00 10,00 User: Innowep Date of measurement: 27/10/2009, 14:26 Comment: H155 - gestrichen Feld 4 - Scratch+MF 2	Number of data points	Permanent deformation		Elastic deformation		Total deformation		Friction force		Frict. coef. µ			
	Loads/mN	Mean/µm	Stand. dev./µm	Mean/µm	Stand. dev./µm	Mean/µm	Stand. dev./µm	Mean/mN	Stand. dev./mN	Mean	Stand. dev.	Filter: Low pass	
	1,00	0,88	0,593	-0,17	0,283	0,72	0,535	1,23	0,445	1,22	0,448		
	2,00	2,27	1,90	0,08	0,278	1,98	0,857	3,08	0,596	1,54	0,302		
	3,00	227	2,35	0,815	0,16	0,347	2,51	0,891	4,33	0,830	1,44	0,278	Cutoff: 0,030 mm
	4,00	227	2,96	1,155	0,27	0,388	3,23	0,943	5,81	0,787	1,45	0,193	
	5,00	227	2,83	1,424	0,46	0,412	3,30	1,342	7,16	1,479	1,43	0,296	
	6,00	227	1,90	1,431	0,68	0,304	2,57	1,364	7,68	2,252	1,28	0,375	
	7,00	227	4,22	2,071	0,68	0,545	4,89	1,806	10,31	2,347	1,47	0,335	
	8,00	227	4,67	1,429	0,93	0,472	5,60	1,229	11,93	1,349	1,49	0,168	
	9,00	227	5,86	2,709	0,73	0,551	6,60	2,531	13,85	2,651	1,54	0,294	
	10,00	228	4,76	3,881	1,10	0,792	5,86	3,383	14,07	4,463	1,41	0,446	
User:		0,00	0	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,000	
Date of measurement:		0,00	0	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,000	
Comment:		0,00	0	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,000	
H155 - gestrichen Feld 4 - Scratch+MF 2		0,00	0	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,00	0,000	
Total mean:		2524	3,21	2,367	0,49	0,595	3,70	2,444	1,43	0,338	1,43	0,338	


Sample FFF




UST ®												
Load/mN	Number of data points		Permanent deformation		Elastic deformation		Total deformation		Friction force		Frict. coef. µ	
	Mean/µm	Stand. dev./µm	Mean/µm	Stand. dev./µm	Mean/µm	Stand. dev./µm	Mean/µm	Stand. dev./µm	Mean/mN	Stand. dev./mN	Mean	Standard dev.
1,00	253	1,51	0,342	0,61	0,147	0,09	0,267	1,80	0,389	1,79	0,376	Filter: Low pass
2,00	227	2,57	0,482	-0,40	0,193	2,17	0,409	4,66	0,462	2,32	0,233	Cutoff:
3,00	227	3,61	0,614	-0,37	0,237	3,25	0,545	6,68	0,604	2,23	0,200	mm
4,00	227	4,83	0,666	-0,48	0,274	4,15	0,635	8,53	0,595	2,13	0,150	
5,00	227	5,60	0,638	-0,23	0,222	5,37	0,595	11,69	0,837	2,33	0,162	
6,00	227	6,54	0,886	0,15	0,266	6,89	0,886	13,85	0,872	2,31	0,147	
7,00	227	7,28	0,979	0,23	0,313	7,52	0,956	16,02	1,400	2,29	0,202	
8,00	227	8,53	1,256	0,09	0,272	8,83	1,132	17,62	1,717	2,20	0,214	
9,00	227	8,72	0,740	0,36	0,254	9,06	0,749	19,45	1,029	2,16	0,113	
10,00	228	7,78	1,898	0,81	0,377	8,38	1,827	19,87	2,358	1,99	0,236	
0,00	0	0,00	0,000	0,00	0,000	0,00	0,000	0,00	0,000	0,00	0,000	
User: Innowep												
Date of measurement: 27/10/2009, 11:22												
Comment: T7032 - gestrichen Feld 5 - Scratch+MF 1												
Total mean:	2524	5,66	2,579	-0,06	0,488	5,60	2,891	2,17	0,269	2,17	0,272	

6.3 Measurement window “Abrasion”

Sample CCC




Sample FFF




6.4 Measurement window “Micro friction”

Sample CCC (example)




FFF (example)




6.5 Measurement window “Roughness”

Sample CCC (example)




FFF (example)




6.6 Measurement window “Static measurement”

CCC





FFF




6.7 3D standard measurement


CCC, overview of surface profiles and deformations



CCC, 1st measuring step





INNOWEP GmbH 3D Standard measurement Measuring & Testing




INNOWEP GmbH 3D Standard measurement Measuring & Testing


CCC, 2nd measuring step



CCC, 3rd measuring step





INNOWEP GmbH 3D Standard measurement Measuring & Testing





INNOWEP GmbH 3D Standard measurement Measuring & Testing



CCC, permanent deformation




CCC, elastic deformation




CCC, total deformation



FFF, overview of surface profiles and deformations





INNOWEP GmbH 3D Standard measurement Measuring & Testing





INNOWEP GmbH 3D Standard measurement Measuring & Testing



FFF, 1st measuring step





FFF, 2nd measuring step





FFF, 3rd measuring step





FFF, permanent deformation



FFF, elastic deformation





FFF, total deformation




6.8 3D topography


CCC



FFF



INNOWEP GmbH 3D Topography Measuring & Testing



INNOWEP GmbH 3D Topography Measuring & Testing